

Standard Symbol

#### **BMP Objectives**

- Soil Stabilization
- Sediment Control
- Tracking Control
- O Wind Erosion Control
- Non-Storm Water Management
- Materials and Waste Management

# Definition and Purpose

A tire wash is an area located at stabilized construction access points to remove sediment from tires and undercarriages, and to prevent sediment from being transported onto public roadways.

## Appropriate Applications

- Tire washes may be used on construction sites where dirt and mud tracking onto public roads by construction vehicles may occur.
- This BMP may be implemented on a project-by-project basis with other BMPs when determined necessary and feasible by the Resident Engineer (RE).

#### Limitations

- Requires a supply of wash water.
- Requires a turnout or doublewide exit to avoid having entering vehicles drive through the wash area.

# Standards and Specifications

- Incorporate with a stabilized construction entrance/exit. See BMP TC-1, "Stabilized Construction Entrance/Exit."
- Construct on level ground when possible, on a pad of coarse aggregate, greater than 75 mm (3 inches) and smaller than 150 mm (6 inches). A geotextile fabric shall be placed below the aggregate.
- Wash rack shall be designed and constructed/manufactured for anticipated traffic loads.
- Provide a drainage ditch that will convey the runoff from the wash area to a sediment trapping device. The drainage ditch shall be of sufficient grade, width, and depth to carry the wash runoff.


### **Entrance/Outlet Tire Wash**




- Require all employees, subcontractors, and others that leave the site with mud-caked tires and/or undercarriages to use the wash facility.
- Implement BMP SC-7, "Street Sweeping and Vacuuming" as needed.
- Use of constructed or prefabricated steel plate with ribs for entrance/exit access is allowed with written approval of RE.

#### Maintenance and Inspection


- Remove accumulated sediment in wash rack and/or sediment trap to maintain system performance.
- Inspect routinely for damage and repair as needed.



#### SECTION A-A NOT TO SCALE



### SECTION B-B



TYPICAL TIRE WASH NOT TO SCALE